



**1/4" SONY HAD CCD**

**27X Optical Zoom, 10X Digital Zoom**

### Parameters

Image Sensor	1/4" SONY HAD CCD
Horizontal Resolution	480TVL
System Signal	NTSC
Lens	27X Optical Zoom, 10X digital zoom , f=3.2~96mm
Minimum Illumination	0.01 Lux
Black Light Compensation	ON/OFF
S/N Ratio	>50dB
Electronic Shutter	1/50~1/10000 s
Auto Focus	Auto
White Balance	Auto
Focus Mode	Auto / Manual
Video Output	1.0Vp-p,75Ω

### Technical Index

Pan Angle	0°~360°
Tilt Angle	0°~90° & 180 ° In Auto Flip
Rotation Speed	0.5°/s~240°/s
Preset Point	256, Each Preset is programmable
Cruise Tracking Group	3 Groups
Manual Menu	OSD Menu
Power Source	24V AC, 50/60HZ
Communication	Standard RS485
Baud Rate	1200/2400/4800/9600 Optional
Shell	Aluminium Alloy
Protection Grade	Weather Proof Housing, TVS1500W Lightning Proof Surge Proof
Temperature	-40℃~60℃(-40°F~140°F) Build-in Colling Fan & Heater
Installation Option	Wall Mounting Bracket, Suspending Installation Bracket, In- ceiling
Package Size	410*330*330mm